



HEX SLOTTED NUTS														ANSI/ASME B18.2.2
Nominal Size or Basic Major Diameter of Thread	F			G		H			T		S		Runout of Bearing Surface FIM	
	Width Across Flats			Width Across Corners		Thickness			Unslotted Thickness		Width of Slot			
	Basic	Max	Min	Max	Min	Basic	Max	Min	Max	Min	Max	Min		
1/4	0.2500	7/16	0.438	0.428	0.505	0.488	7/32	0.226	0.212	0.14	0.12	0.10	0.07	0.015
5/16	0.3125	1/2	0.500	0.489	0.577	0.557	17/64	0.273	0.258	0.18	0.16	0.12	0.09	0.016
3/8	0.3750	9/16	0.562	0.551	0.650	0.628	21/64	0.337	0.320	0.21	0.19	0.15	0.12	0.018
7/16	0.4375	11/16	0.688	0.675	0.794	0.768	3/8	0.385	0.365	0.23	0.21	0.15	0.12	0.018
1/2	0.5000	3/4	0.750	0.736	0.866	0.840	7/16	0.448	0.427	0.29	0.27	0.18	0.15	0.019
9/16	0.5625	7/8	0.875	0.861	1.010	0.982	31/64	0.496	0.473	0.31	0.29	0.18	0.15	0.020
5/8	0.6250	15/16	0.938	0.922	1.083	1.051	35/64	0.559	0.535	0.34	0.32	0.24	0.18	0.021
3/4	0.7500	1-1/8	1.125	1.088	1.299	1.240	41/64	0.665	0.617	0.40	0.38	0.24	0.18	0.023
7/8	0.8750	1-5/16	1.312	1.269	1.516	1.447	3/4	0.776	0.724	0.52	0.49	0.24	0.18	0.025
1	1.0000	1-1/2	1.500	1.450	1.732	1.653	55/64	0.887	0.831	0.59	0.56	0.30	0.24	0.027
1-1/8	1.1250	1-11/16	1.688	1.631	1.949	1.859	31/32	0.999	0.939	0.64	0.61	0.33	0.24	0.030
1-1/4	1.2500	1-7/8	1.875	1.812	2.165	2.066	1-1/16	1.094	1.030	0.70	0.67	0.40	0.31	0.033
1-3/8	1.3750	2-1/16	2.062	1.994	2.382	2.273	1-11/64	1.206	1.138	0.82	0.78	0.40	0.31	0.036
1-1/2	1.5000	2-1/4	2.250	2.175	2.598	2.480	1-9/32	1.317	1.245	0.86	0.82	0.46	0.37	0.039
2	2.0000	3	3.000	2.900	3.464	3.306	1-23/32	1.759	1.679	1.24	1.20	0.52	0.43	0.048

<b>Description</b>	Hex nut with opposed slots cut into the top of the nut through the centers of the flats. The slots are on the end opposite the bearing surface.
<b>Applications/ Advantages</b>	The slots are for the insertion of a cotter pin to secure the nut when used with a drilled shank fastener.
<b>Material</b>	Nuts shall be made from a low-carbon steel which conforms to the following chemical composition requirements-- <b>Carbon:</b> 0.47% max.; <b>Phosphorus:</b> 0.12% max.; <b>Sulfur:</b> 0.23% max..
<b>Hardness</b>	Rockwell C32 maximum
<b>Proof Load</b>	72,000 psi.
<b>Plating</b>	See Appendix-A for plating information.